


Power-Lock™ Hospital Use Locking Devices

2-Pole, 3-Wire Grounding
20A, 125V/AC
Non-NEMA




20A, 125V/AC Non-NEMA

Hospital Use Power-Lock Plugs & Connectors

Style & Description	Cord Dia.	Catalog No.		Certifications				
		Plug	Connector	US	CS	UK	US	US
Nylon Back Wired "Dead Front" Design, Gray	0.33-0.66" (8.4-16.7mm)	□ 23056N	□ 23054N	•				•
Armored Back Wired "Dead Front" Design, Gray	0.33-0.66" (8.4-16.7mm)	□ 23056	□ 23054	•				•



23054




23050

Hospital Use Power-Lock Receptacles

Style & Description	Catalog No.		Certifications				
	Single Receptacle		US	CS	UK	US	US
Receptacle, not for use in Hazardous Areas	□ 23050		•	•			•

Power-Lock™ Hospital Use Mobile X-Ray™ Devices

2-Pole, 3-Wire Grounding
50A, 250V/AC
Non-NEMA



50A, 250V/AC Non-NEMA

Hospital Use Power-Lock Plugs


Style & Description	Cord Dia.	Catalog No.		Certifications				
		Plug		US	CS	UK	US	US
Back Wired "Dead Front" Design, Gray	0.75-1.25" (19.1-31.8mm)	□ 25525		•				•



25525

Hospital Use Power-Lock Receptacles

Style & Description	Catalog No.		Certifications				
	Single Receptacle		US	CS	UK	US	US
Receptacle in Plate Assembly, Stainless Steel	□ 25505		•	•			•



25505

Icon Key

NAFTA Compliant - see page O-30

Accessories for Power-Lock Hospital Use Locking Devices

Description	Catalog No.	
Steel 50A receptacle wallbox, KO sizes 1.25" (31.9mm), 1.50" (38.1mm), 2" (50.8mm)	□ 25509	•



25509

Dimensional Information: C-85
Plug Specification Information:
Hospital Power-Lock: C-102

Receptacle Specification Information:
Hospital Power-Lock: C-102